

GB

1. PRODUCT DESCRIPTION

System component compatible with Gerriets water-based seals and specific parquet seals as indicated in the respective application areas. Enhances slip resistance by creating a light surface texture, significantly increasing floor traction. To be applied as the final layer in the coating system application.

Features:

- Liquid preparation for simplified application
- Effective result
- Tested according to DIN 51130, slip resistance class R10 (VARIOSeal / VARIOColour Satin Matte / Extra Matte)
- When used with this additive, tested according to BS 7976-2, meeting the UK Slip Resistance Group's recommendations for slip accident prevention under dry and wet conditions
- Emission-tested construction product according to AgBB guidelines, abZ-No. Z-157.20-69 (Germany)

Note: Suitability for specific safety floorings, floating floors, highly textured surfaces, and raised nodules should be checked based on individual project requirements.

2. APPLICATION

- **Preparation:** Shake well.
- **Mixing ratio:** 10:1. Carefully and evenly mix VARIOHold with the base coat. Then add the appropriate amount of hardener for the base coat.
- **Application:** Follow the application instructions for the respective coating system.

Notes:

- Using in lower layers does not affect the seal's functionality but will not be effective.
- Prepare enough coating to apply a complete layer over the surface. Additional mixing may result in visible quality variations.

3. CONSUMPTION

- **Mixture:** 50 ml/m² (20 m²/l)
- **Recommended coating:** 50 ml/m² with a mixing ratio of 5 ml/m² (Coverage: 100 m²/0.5 l)

Deviations are possible but do not meet slip resistance report requirements.

4. DRYING TIME

As described for the base system.

5. STORAGE

Protect from frost. Store in a cool, dry place, out of reach of children.

- **Shelf life:** 24 months in unopened original packaging from the manufacturing date. Observe the marked manufacturing date.

6. TECHNICAL DATA

- **Ingredients:** Water, Polyacrylate, Glycol Ether, Silica, Waxes, Additives, Preservatives
- **Safety:**
 - ADR/RID: Not classified as dangerous goods for transport
 - CLP/GHS: No labeling required, UFI: 0CJ0-E067-D00Y-FUT5

For more information on safe handling, refer to the safety data sheet. Even with low-emission products, take usual precautions. Keep out of children's reach. Empty containers can be disposed of as household waste or recycled.

7. CROSS REFERENCES

Our current publications are part of this data sheet:

- General instructions for using Gerriets surface products.
- Safety data sheet available on request.

For more information, visit our website: www.gerriets.com.

Gerriets GmbH

Germany
Contact: info@gerriets.com
www.gerriets.com

This technical advice is provided to the best of our knowledge and the latest technological standards. No damage is expected when used as directed. However, usage is at your own responsibility and requires a prior check of the product's suitability for each specific application. Our advice is therefore non-binding and cannot be invoked as a basis for liability.